



PRIMEKOTE

EXTERIOR ALKYD PRIMER

111

PREMIUM SERIES
EXTERIOR
FLAT
111
PRIMEKOTE

PRIMEKOTE is a premium exterior alkyd wood primer designed for tannin blocking and superior, long-lasting adhesion to wood surfaces. This high solids, slow drying alkyd primer provides deep penetration on weathered wood surfaces for maximum hide and holdout. The high-solids formulation provides exceptional hide while blocking tannins and other extractive bleeding from leeching into subsequent finish coats.

PRIMEKOTE is intended for use on both new and previously painted wood, hardboard, and manufactured wood surfaces. This premium exterior primer is the ideal primer for cedar, redwood and other species prone to extractive bleeding. Can be top-coated with both alkyd and acrylic finishes.

COMPLIANCE & CERTIFICATION

Gloss Level	1
VOC Content	337 g/L 2.81 lb./Gal

PERFORMANCE & FEATURES

- Long-Oil Primer
- Excellent Tannin Blocker
- Superior Adhesion
- High Solids Formula

BENEFITS

Long-Oil Primer: This rugged long-oil primer allows for superior penetration to new and weathered wood surfaces providing protection from chipping, peeling, and bubbling finish coats.

High Solids Primer: This high solids primer has exceptional wet and dry hide providing a sound base for traditional exterior finishes.

Stain Blocking Technology: PRIME KOTE provides maximum protection from nail head flash rust and tannin bleed on species like cedar and redwood.

PRODUCT SPECIFICATIONS

Vehicle Type: Alkyd-Oil

Color Tinting: White. May be tinted, up to 2 oz. per gallon, with low VOC colorants.

Gloss: Flat

0-5 units @ 60°

Solid Content: Weight: 76% ± 2

Volume: 57% ± 2

Drying Time: (75° F. & 50% R.H.)

To touch: 4 Hours

To recoat: Overnight

Extended drying time may be expected when conditions such as high humidity, high dew point, low temperature, etc. are present. Allow product to dry thoroughly before top coating

Theoretical Coverage:

Apply at 400 sq. ft./gal. to achieve

4.0 mils Wet Film Thickness

2.2 mils Dry Film Thickness

When calculating working coverage, allow for application losses, texture and porosity of surface, application technique, etc.

PRECAUTIONS/LIMITATIONS

- Contains linseed oil. Rags or clothing soaked with this product should be immersed entirely in water until disposal to prevent spontaneous combustion.
- Please refer to Safety Data Sheets.
- Apply only if air, surface and material temperatures remain 50° F or above during application and drying.
- Should be topcoated within 30 days of application.



PRIMEKOTE

EXTERIOR ALKYD PRIMER

111

PREMIUM SERIES
EXTERIOR
FLAT
111
PRIMEKOTE

SURFACE PREPARATION

Surfaces must be dry, clean and free of dust, dirt, grease, oil or any other contaminants that may prevent proper adhesion. All loose paint must be removed and glossy surfaces dulled by sanding. Plaster surfaces must be well cured, and porous masonry surfaces should be filled with block filler. Tape joints and nailheads on drywall should be sanded and dusted clean before finishing. Mud on joints and nailheads must be thoroughly cured before finishing to help avoid photographing. Galvanized surfaces shall have all oils removed prior to application of coating.

Warning! If you scrape, sand or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage, especially in children. Pregnant women should also avoid exposure. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the national lead information hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

HALLMAN LINDSAY FINISHING RECOMMENDATIONS

High-Performance Acrylic: DURATECH Series

Designer Finish: GENERATION Series

Premium Finish: WEATHERGUARD Series

Professional Finish: DURA KOTE Series

Stain Finishes: TIMBERSHADES 188, TIMBERSHADES 185

APPLICATION

Mix thoroughly before use. Apply by airless spray for best results. May be applied by brush or roller; however, all properties related to hide and appearance may be affected. Flow and leveling is best achieved by applying a full, uniform coating and working to a wet edge using overlapping strokes. Do not brush or roll excessively. Surfaces should be dry prior to paint application. All products are formulated ready for application. If needed, thin sparingly and do not exceed 2oz per gallon. Clean all applicators with mineral spirits immediately after use.

EQUIPMENT REQUIREMENTS

Airless: Minimum .70 GPM, 23000 PSI, .019-.021" Tip

HVLP: Twin-stage turbine, 5 – 8 PSI, .051 to .070 projector set

Roller: 1/2"–3/4" nap shed-resistant cover or lambswool cover

Brush: Natural China Bristle or Synthetic Blend