

GRIPCRETE FILL & FINISH is designed to provide efficiencies and cost saving measures when coating concrete block, precast, and other masonry surfaces. The single use, high-building products reduce labor and material costs by filling, sealing, and finishing masonry surfaces in two coats instead of traditional three-coat systems. When applied properly, these products will create a smooth, pinhole-free finish that beautifies and protects masonry surfaces.

GRIPCRETE FILL & FINISH is formulated for easy and efficient finishing of masonry surfaces. The attractive satin finish provides lasting protection and application efficiencies for commercial and light industrial surfaces. Designed for application to masonry surfaces, these products can be applied to new and repainted block, brick, concrete and other masonry surfaces.

COMPLIANCE & CERTIFICATION

Gloss Level	4
VOC Content	111 g/L 0.92 lb./Gal

RECOMMENDED USAGE

- For Interior and Exterior Use
- Block, Brick, Concrete, and Similar Masonry Surfaces

PERFORMANCE & FEATURES

- Efficient Coating System
- Lasting Protection & Finish
- 100% Acrylic High-Build Finish
- Interior & Exterior Coating

BENEFITS

Increased Efficiencies: Complete jobs faster with a single-source product that primes, fill, seals, and finishes porous masonry surfaces in fewer coats.

100% Acrylic Formula: All acrylic resin provides exceptional UV protection, improved dirt pick-up, and mildew resistance for increased longevity on exposed surfaces.

Easy Application: Formulated for brush, roll, and spray application, FILL & FINISH can be used on jobs ranging from finishing large, unoccupied spaces to rolling residential foundations.

PRODUCT SPECIFICATIONS

Vehicle Type: 100% Acrylic

Color Tinting: Pro White. May be tinted, up to 2 oz. per gallon, with low VOC colorants.

Gloss: Satin

25-35 @ 60°

Solid Content: Weight: 53% ± 2

Volume: 42% ± 2

Drying Time: (75° F. & 50% R.H.)

To touch: 1 Hour

To recoat: Overnight

Extended drying time may be expected when conditions such as high humidity, high dew point, low temperature, etc. are present. Allow product to dry thoroughly before top coating

Theoretical Coverage:

Apply at 80-100 sq. ft./gal. to achieve

15-20 mils Wet Film Thickness

6.0-8.0 mils Dry Film Thickness

When calculating working coverage, allow for application losses, texture and porosity of surface, application technique, etc.

PRECAUTIONS/LIMITATIONS

- Please refer to Safety Data Sheets.
- Not suited for areas of extreme hydrostatic pressure. Not intended as a below-grade waterproofing system.
- Apply only if surface and paint temperatures are above 50° F and will remain so for 48 hours. Dew point must not be within 5° of the temperature until film is dry.



GRIPCRETE

HD FILL & FINISH

182

PREMIUM SERIES
INTERIOR/EXTERIOR
SATIN
182
HD FILL & FINISH

SURFACE PREPARATION

Surfaces must be dry, clean and free of dust, dirt, grease, oil or any other contaminants that may prevent proper adhesion. All loose paint must be removed and glossy surfaces dulled by sanding. Plaster surfaces must be well cured, and porous masonry surfaces should be filled with block filler. Tape joints and nailheads on drywall should be sanded and dusted clean before finishing. Mud on joints and nailheads must be thoroughly cured before finishing to help avoid photographing. Galvanized surfaces shall have all oils removed prior to application of coating.

Warning! If you scrape, sand or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage, especially in children. Pregnant women should also avoid exposure. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the national lead information hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

HALLMAN LINDSAY FINISHING RECOMMENDATIONS

Interior

High-Performance Acrylic: AQUAPOXY1, DURATECH, and MULTI-SURFACE ACRYLIC Series

Designer Finish: PURE and LUSTRE Series

Premium Finish: WONDERKOTE and EARTHSCAPES Series

Professional Finish: PRO KOTE and RENEWAL Series

Exterior

High-Performance Acrylic: MULTI-SURFACE ACRYLIC and DURATECH Series

Designer Finish: GENERATION Series

Premium Finish: WEATHERGUARD Series

Professional Finish: DURA KOTE SERIES

APPLICATION

Mix thoroughly before use. Designed for airless spray application. To achieve optimum performance from coating, apply two (2) coats of 182-1 at 80-100sq.ft. per gallon. Spray and backroll both applications, pushing the coating into the surface. May be brushed and rolled. Flow and leveling is best achieved by applying a full, uniform coating and working to a wet edge using overlapping strokes. Surfaces should be dry prior to paint application. All products are formulated ready for application. If needed, thin sparingly and do not exceed 2oz per gallon. Clean all applicators with water immediately after use.

EQUIPMENT REQUIREMENTS

Airless: Minimum 1 GPM, 2500 PSI, .025-.029" Tip

HVLP: Not Recommended

Roller: 1/2" - 1" nap shed-resistant or lambswool cover

Brush: 100% Nylon or Synthetic Blend