



TIMBERSHADES

SEMI-TRANSPARENT EXTERIOR ALKYD STAIN

197

DESIGNER SERIES
EXTERIOR
SEMI-TRANSPARENT
197
TIMBERSHADES
ALKYD

RUSTIC STAIN ALKYD SEMI-TRANSPARENT is our original exterior semitransparent deck and siding stain designed to highlight the natural beauty of wood surfaces. The deep penetrating formula provides a durable, water repellent finish that can withstand steady exposure and foot traffic. Easy single coat application allows for easy maintenance and woodcare for years to come.

RUSTIC STAIN ALKYD SEMI-TRANSPARENT is formulated for exterior use on prepared wood surfaces including decks, siding, fences, and play-sets. It may be used on both new and most previously stained cedar, pine, redwood, log, half-log, shake, and other wood surfaces.

COMPLIANCE & CERTIFICATION

Gloss Level	1
VOC Content	522 g/L 4.36 lb./Gal

RECOMMENDED USAGE

- For Exterior Use
- New and Previously Stained Surfaces
- Decks and Fencing
- Siding, Half-Log, and Shake

PERFORMANCE & FEATURES

- Hydrophobic Technology
- Rich and Natural Pre-Mixed Colors
- Single Coat Application
- Enhanced Natural Appearance

BENEFITS

Rich and Natural Colors: Pre-mixed cedartone colors use trans-oxide pigments to provide rich, natural wood tones.

Water Repellent Finish: Special hydrophobic technology repels water to help extend the life of exterior surfaces.

Easy Application: Easy single-coat application provides an enhanced natural appearance that will never peel or flake off when applied properly.

PRODUCT SPECIFICATIONS

Vehicle Type: Linseed Oil / Alkyd

Color Tinting: Ready-Mixed Colors and Tinting Bases

Gloss: Flat

0-5 units @ 60°

Solid Content: Weight: 39% ± 2

Volume: 35% ± 2

Drying Time: (75° F. & 50% R.H.)

To touch: 24 Hours

To recoat:

Extended drying time may be expected when conditions such as high humidity, high dew point, low temperature, etc. are present. Allow product to dry thoroughly before top coating.

Theoretical Coverage:

Apply at 300-400 sq. ft./gal. to achieve
When calculating working coverage, allow for application losses, texture and porosity of surface, application technique, etc.

PRECAUTIONS/LIMITATIONS

- Contains linseed oil. Rags or clothing soaked with this product should be immersed entirely in water until disposal to prevent spontaneous combustion
- Please refer to Safety Data Sheets.
- Apply only if air, surface and material temperatures remain 50° F or above during application and drying.



TIMBERSHADES

SEMI-TRANSPARENT EXTERIOR ALKYD STAIN

197

DESIGNER SERIES
EXTERIOR
SEMI-TRANSPARENT
197
TIMBERSHADES
ALKYD

SURFACE PREPARATION

STAIN MUST BE ABLE TO PENETRATE THE WOOD FOR PROPER PERFORMANCE. Wood surfaces must be dry, clean and free of dirt, oil, chalk, or any other contaminants. If water is used to clean the wood, allow the deck or siding to dry completely before application of the stain. To determine the application method that will insure maximum penetration of NATURAL STAIN FINISH, test a patch in an inconspicuous area. If there is no sheen when the stain is dry, it should be able to penetrate the rest of the deck surface; follow the SPECIFICATION: "POROUS WOOD" instructions below. If the stain remains tacky or there is a sheen when it dries, it was not able to penetrate the surface and the wood must be sanded. Follow the SPECIFICATION: "NON-POROUS WOOD" instructions below. NOTE: stain may take differently on different areas due to varied exposure, grain patterns, types of wood, etc. Several test patches may be necessary.

Warning! If you scrape, sand or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage, especially in children. Pregnant women should also avoid exposure. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the national lead information hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

HALLMAN LINDSAY PRIMING RECOMMENDATIONS

New Wood Surfaces: Cedar, Redwood, Pine, Treated Pine: Apply TIMBERSHADES 197 to achieve desired appearance.

Recoating Wood Surfaces: Spot prime all

APPLICATION

Mix thoroughly before use and periodically during application. Apply by brush, roller, or "Hudson" type garden sprayer, or airless sprayer set at low pressure. If spray applied, should be back-rolled or brushed to ensure maximum penetration and uniform appearance. DO NOT ALLOW TO PUDDLE. Avoid lap marks by applying to entire length of 2 or 3 boards, working from a stained to unstained area. Applying only if air, surface, and product temperatures remain 50° F or higher during application and drying time. DO NOT APPLY IN DIRECT SUNLIGHT. All products are formulated ready for application. If needed, thin sparingly and do not exceed 2oz per gallon. Clean all applicators with mineral spirits immediately after use.

EQUIPMENT REQUIREMENTS

Airless: Minimum .50 GPM, 1800 PSI, .011-.013" Tip

HVLP: Not Recommended

Roller: 1/4" - 3/4" nap lambswool cover

Brush: 100% Nylon or Synthetic Blend