



FARM & RANCH

EGGSHELL EXTERIOR ACRYLIC BARN PAINT - RED

203

PREMIUM SERIES
EXTERIOR
EGGSHELL
203
FARM & RANCH

FARM AND RANCH LATEX is our professional line of agricultural exterior paints. Designed for professional use, these latex finishes allow for faster spray application without compromising film-build. Self-priming technology allows fast production and same-day finishing. Factory tinted to match the classic barn red and white colors produces exceptional coverage that resists chalking and fading.

Our FARM AND RANCH LATEX products have been trusted to protect and beautify Wisconsin's family farms for decades. With updated adhesion qualities, they can be applied to old and new barn boards and prepared metal siding. It can be used on many projects including barns, out buildings, bins, fences, and more.

COMPLIANCE & CERTIFICATION

Gloss Level	3
VOC Content	29 g/L 0.24 lb./Gal

PERFORMANCE & FEATURES

- Easy Application
- Self-Priming Finish
- Pre-Mixed Red & White
- Hybrid Acrylic-Alkyd Resin

BENEFITS

Easy Application: The full-bodied formula provides a high hiding finish for easier finishing whether on a ladder brushing trim or spraying from a boom lift.

Pre-Mixed Colors: Pre-Mixed colors provide exceptional coverage and color retention on weathered wood creating a bright, clean finish that resist chalking.

Self-Priming Finish: Unique hybrid resin allows the same product to be prime and finish wood and masonry surfaces helping to simplify any painting project.

PRODUCT SPECIFICATIONS

Vehicle Type: Acrylic-Alkyd

Color Tinting: Red. Do Not Tint.

Gloss: Eggshell

6-12 units @ 60°

Solid Content: Weight: 46% ± 2

Volume: 33% ± 2

Drying Time: (75° F. & 50% R.H.)

To touch: 1 Hour

To recoat: 2 Hours

Extended drying time may be expected when conditions such as high humidity, high dew point, low temperature, etc. are present. Allow product to dry thoroughly before top coating.

Theoretical Coverage:

Apply at 330 sq. ft./gal. to achieve

4.0 mils Wet Film Thickness

1.3 mils Dry Film Thickness

When calculating working coverage, allow for application losses, texture and porosity of surface, application technique, etc.

PRECAUTIONS/LIMITATIONS

- Please refer to Safety Data Sheets.
- Apply only if air, surface and material temperatures remain 50° F or above during application and drying.



FARM & RANCH

EGGSHELL EXTERIOR ACRYLIC BARN PAINT - RED

203

PREMIUM SERIES
EXTERIOR
EGGSHELL
203
FARM & RANCH

SURFACE PREPARATION

Surfaces must be dry, clean and free of dust, dirt, grease, oil or any other contaminants that may prevent proper adhesion. All loose paint must be removed and glossy surfaces dulled by sanding. Plaster surfaces must be well cured, and porous masonry surfaces should be filled with block filler. Tape joints and nailheads on drywall should be sanded and dusted clean before finishing. Mud on joints and nailheads must be thoroughly cured before finishing to help avoid photographing. Galvanized surfaces shall have all oils removed prior to application of coating.

Warning! If you scrape, sand or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage, especially in children. Pregnant women should also avoid exposure. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the national lead information hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

HALLMAN LINDSAY PRIMING RECOMMENDATIONS

Wood Surfaces: Self Priming (requires 2 coats); PRIMEKOTE, 111 for Cedar and Redwood. All other species optional PRIMEGUARD, 112.

Aluminum Siding: Self Priming (requires 2 coats) or METALGUARD ACRYLIC DTM Primer/Finish, 338.

Galvanized Metal: Self Priming (requires 2 coats) or METALGUARD ACRYLIC DTM Primer/Finish, 338.

Steel: METALGUARD Rust Inhibitive Primer, 330.

CMU, Concrete Block and Split Face: GRIPCRETE HD Block Filler, 181.

Masonry/Stucco: Self Priming or GRIPCRETE Masonry/Plaster Primer, 166.

APPLICATION

Apply by airless spray and back roll with a 1/2 inch nap roller for best results. May be applied by brush or roller; however, all properties related to hide and appearance may be affected. Surfaces should be dry prior to paint application. If needed, thin sparingly and do not exceed 2oz per gallon. Clean all applicators with water immediately after use.

EQUIPMENT REQUIREMENTS

Airless: Minimum .70 GPM, 2500 PSI, .017-.019" Tip

HVLP: Not Recommended

Roller: 1/2" - 1" nap synthetic cover

Brush: 100% Nylon or Synthetic Blend