



# LUSTRE

## SATIN INTERIOR 100% ACRYLIC WALL FINISH

### 285

DESIGNER SERIES  
INTERIOR  
SATIN  
285  
LUSTRE

LUSTRE KOTE is a premium interior wall finish designed to provide elegance and durability to homes and offices. Paint glides off the brush and roller for easy, buttery application that reduces roller stipple and brush marks for a rich, full-bodied appearance. The 100% acrylic formula offers tough protection for repeated washing and stain resistance allowing most spots and blemishes to wipe off with soap and water.

LUSTRE KOTE is formulated to create premium wall finishes with silky, smooth application qualities. The exceptional durability of the 100% acrylic resin makes it ideal for areas that are subject to heavy use including offices, hallways, baths, kitchens, and classrooms. Apply these products on brush and roll residential and office painting projects requiring a distinguished finish.

#### COMPLIANCE & CERTIFICATION

Gloss Level	4
VOC Content	124 g/L 1.03 lb./Gal

#### RECOMMENDED USAGE

- For Interior Use
- Offices and Classrooms
- Hallways, Bathrooms, and Kitchens

#### PERFORMANCE & FEATURES

- 100% Acrylic Formula
- Silky Application
- Premium Coverage
- Exceptional Durability

#### BENEFITS

**100% Acrylic Formula:** The all-acrylic formula provides a premium scrubbable surface that repels stains, extending the life of the finish.

**Silky Application:** The silky, buttery application allows paint to glide off the brush and roller during application. This easy-to-apply finish produces a truly elegant finish.

**Faster Custom Colors:** Designed for application and coverage, the high-hiding nature allows for faster color changes and blocking of previous coatings.

#### PRODUCT SPECIFICATIONS

**Vehicle Type:** 100% Acrylic  
**Color Tinting:** White and Tint Bases  
**Gloss:** Satin

15-25 units @ 60°

**Solid Content:** Weight: 47% ± 2  
Volume: 35% ± 2

**Drying Time:** (75° F. & 50% R.H.)  
To touch: 1 Hour  
To recoat: 4 Hours

*Extended drying time may be expected when conditions such as high humidity, high dew point, low temperature, etc. are present. Allow product to dry thoroughly before top coating*

#### **Theoretical Coverage:**

Apply at 400 sq. ft./gal. to achieve  
4.0 mils Wet Film Thickness  
1.6 mils Dry Film Thickness

*When calculating working coverage, allow for application losses, texture and porosity of surface, application technique, etc.*

#### PRECAUTIONS/LIMITATIONS

- Please refer to Safety Data Sheets.
- Apply only if air, surface and material temperatures remain 50° F or above during application and drying.

# LUSTRE

## SATIN INTERIOR 100% ACRYLIC WALL FINISH

### 285

DESIGNER SERIES  
INTERIOR  
SATIN  
285  
LUSTRE

### SURFACE PREPARATION

Surfaces must be dry, clean and free of dust, dirt, grease, oil or any other contaminants that may prevent proper adhesion. All loose paint must be removed and glossy surfaces dulled by sanding. Plaster surfaces must be well cured, and porous masonry surfaces should be filled with block filler. Tape joints and nailheads on drywall should be sanded and dusted clean before finishing. Mud on joints and nailheads must be thoroughly cured before finishing to help avoid photographing. Galvanized surfaces shall have all oils removed prior to application of coating.

**Warning!** If you scrape, sand or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage, especially in children. Pregnant women should also avoid exposure. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the national lead information hotline at 1-800-424-LEAD (5323) or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### HALLMAN LINDSAY PRIMING RECOMMENDATIONS

New Work

**Drywall:** Pro Wall Primer, 227.

**Plaster/Masonry:** GRIPCRETE Masonry/Plaster Primer, 166.

**Wood:** Enamel Undercoat, 231.

**Galvanized Surfaces:** Self-Priming (requires two coats) or METALGUARD ACRYLIC DTM Primer/Finish, 338.

**Steel Surfaces:** METALGUARD Rust Inhibitive Primer, 330.

**Block:** GRIPCRETE Block Filler, 184.

**Repaint:** Self-Priming (requires two coats).

### APPLICATION

Mix thoroughly before use. Apply by brush, roller, or airless spray or conventional spray. Flow and leveling is best achieved by applying a full, uniform coating and working to a wet edge using overlapping strokes. Do not brush or roll excessively. Surfaces should be dry prior to paint application. Reducing material for spray application should not exceed 10%. All products are formulated ready for application. If needed, thin sparingly and do not exceed 2oz per gallon. Clean all applicators with water immediately after use.

### EQUIPMENT REQUIREMENTS

**Airless:** Minimum .50 GPM, 2600 PSI, .015-.017" Tip

**HVLP:** Twin-stage turbine, 5-8 PSI, .051 to .070 projector set

**Roller:** 1/2" - 3/4" nap synthetic cover

**Brush:** 100% Nylon or Synthetic Blend