



GOAL LINE

READY-MIX EXTERIOR ATHLETIC MARKING PAINT

306

PREMIUM SERIES
EXTERIOR
FLAT
306
GOAL LINE READY-MIX

GOAL LINE READY MIX is a premium, ready-to-use athletic marking paint designed for easy application of bright, crisp lines on natural and synthetic turf. The high hiding bright white finish produces sharp lines with high contrast under natural, LEED, HID and halide lighting. Formulated with increased levels of latex binder extends the longevity of lines reducing the need to replot fields. Local production eliminates sealing and hard-pack providing smooth, clog-free application

GOALLINE READY MIX provides all the same benefits of the concentrate but is pre-diluted 1:1 for easy, no-mix application. This ready-mix product is designed to be applied straight from the bucket eliminating the need for on-site water. GOAL LINE can be used on all athletic fields, tracks, and tennis courts.

COMPLIANCE & CERTIFICATION

Gloss Level	1
VOC Content	< 5 g/L 0.04 lb./Gal

RECOMMENDED USAGE

- For Exterior Use
- Athletic Fields, Tracks, and Tennis Courts

PERFORMANCE & FEATURES

- Long Lasting Lines
- Brighter White
- Clog-Free Application
- Convenient Ready-Mix Formula

BENEFITS

Long Lasting Lines: Long lasting lines keep game and practice fields looking sharp reducing frequency of lining with less replotting of fields.

High-Hiding Formula: High-hiding concentrate provides exceptional coverage for crisper, brighter lines for a pristine game-day appearance.

Local Manufacturing: With local manufacturing, paint will not hard-settle allowing for easier mixing and clog-free spraying. Fast local delivery and volume pricing available.

PRODUCT SPECIFICATIONS

Vehicle Type: Ethylene-Vinyl Acetate

Color Tinting: White. May be tinted, up to 2 oz. per gallon, with low VOC colorants.

Gloss: Flat
0-5 units @ 60°

Solid Content: Weight: 28% ± 2
Volume: 15% ± 2

Drying Time: (75° F. & 50% R.H.)
To touch: 2 Hours

Extended drying time may be expected when conditions such as high humidity, high dew point, low temperature, etc. are present. Allow product to dry thoroughly before top coating

Theoretical Coverage:

Apply at 250-300 sq. ft./gal.

When calculating working coverage, allow for application losses, texture and porosity of surface, application technique, etc.

PRECAUTIONS/LIMITATIONS

- Please refer to Safety Data Sheets.
- Apply only if air, surface and material temperatures remain 50° F or above during application and drying.



GOAL LINE

READY-MIX EXTERIOR ATHLETIC MARKING PAINT

306

PREMIUM SERIES
EXTERIOR
FLAT
306
GOAL LINE READY-MIX

SURFACE PREPARATION

Asphalt should be clean and dry. Dirt or grass surfaces, may be dew laden or slightly damp.

Warning! If you scrape, sand or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage, especially in children. Pregnant women should also avoid exposure. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the national lead information hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

HALLMAN LINDSAY FINISHING RECOMMENDATIONS

Note: Asphalt tracks should be clean and dry. Dirt or grass surfaces may be dew laden or slightly damp.

Grass Surfaces: No priming required. Single coat application.

Other Turf Surfaces: No priming required. Single coat application.

Asphalt Track Surfaces: No priming required. Single coat application.

APPLICATION

Spray Application is best for sharpest lines, produced by making machine. Refer to machine manufacturer's instructions. Roller or brush application is acceptable. 306 Ready-Mix is formulated ready for application. Clean all tools and applicators with water immediately after use.

EQUIPMENT REQUIREMENTS

Airless: Minimum .70 GPM, 2500 PSI, .017-.019" Tip

HVLP: Twin-stage turbine, 5-8 PSI, .051 to .070 projector set

Roller: 1/2" - 3/4" nap synthetic cover

Brush: 100% Nylon or Synthetic Blend