



# BUILDER'S LEGACY

## HI-BUILD VINYL PRIMER/SEALER

350

CLASSIC SERIES

INTERIOR

PRIME COAT

350

HI-BUILD VINYL PRIMER/SEALER

HI-BUILD VINYL PRIMER/SEALER is a production grade primer/sealer designed to prepare new drywall for painting and texturing. The high-building nature fills exceptionally well producing uniform porosity with good enamel hold-out for improved finish coat performance. When sprayed for full coverage, it will provide good wet and dry hide while reducing telegraphing seams and picture framing.

HI-BUILD VINYL PRIMER/SEAL is designed for the high production, value-driven new construction market. Zero-VOC, LEED v4 Credit Eligible formula reduces air quality impact on fellow trades and meets strict air quality standards. Ideally used for residential and commercial production markets and topcoated with Builder's Legacy or Pro Kote interior finishes.

### COMPLIANCE & CERTIFICATION

Gloss Level	1
VOC Content	< 5 g/L < 0.042 lb./Gal

### RECOMMENDED USAGE

- For Interior New Drywall
- Ideal for Priming Prior to Texture and/or Under Flat or Lo-Sheen Finishes.
- Use in Residential and Commercial New Construction

### PERFORMANCE & FEATURES

- Production-Focused Design
- Creates Uniform Surface
- Hi-Build Application
- Zero-VOC
- Can Help Meet LEED v4 Credits

### BENEFITS

**Production-Focused Design:** Fast spraying design fills and seals drywall with a single coat for faster job completion.

### Environmentally Responsible Finish:

This zero-VOC, LEED v4 Credit Eligible finish meets the performance needs of contractors, specifiers, builders, and general contractors looking to meet the strictest air quality standards.

### PRODUCT SPECIFICATIONS

**Vehicle Type:** Ethylene-Vinyl Acetate

**Color Tinting:** White.

**Gloss:** Flat. 0-4 units @ 60°

**Solid Content:** Weight: 41% ± 2  
Volume: 23% ± 2

**Drying Time:** (75° F. & 50% R.H.)

To touch: 1 Hour

To recoat: Overnight

*Extended drying time may be expected when conditions such as high humidity, high dew point, low temperature, etc. are present. Allow product to dry thoroughly before top coating*

### Theoretical Coverage:

Apply at 200 sq. ft./gal. to achieve

8.0 mils Wet Film Thickness

2.3 mils Dry Film Thickness

*When calculating working coverage, allow for application losses, texture and porosity of surface, application technique, etc.*

### PRECAUTIONS/LIMITATIONS

- Please refer to Safety Data Sheets.
- Must be topcoated.
- Joint compound must be completely dry.
- Not intended for use under Epoxy topcoats.
- Apply only if surface and paint temperatures are above 50° F and will remain so for 48 hours. Dew point must not be within 5° of the temperature until film is dry.



# BUILDER'S LEGACY

VINYL PRIMER/SEALER

350

CLASSIC SERIES  
FIRST COAT  
350  
VINYL PRIMER/SEALER

---

## **SURFACE PREPARATION**

On drywall, all taped joints and nail heads should be sanded smooth and dusted. Patch all holes and cracks with an appropriate patching compound. Let dry thoroughly, sand smooth, and prime. Surfaces must be dry, clean, and free of dirt, oil, or any other contaminants.

**Warning! If you scrape, sand or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage, especially in children. Pregnant women should also avoid exposure. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the national lead information hotline at 1-800-424-LEAD (5323) or log on to [www.epa.gov/lead](http://www.epa.gov/lead).**

## **HALLMAN LINDSAY FINISHING RECOMMENDATIONS**

**Designer Finish:** Pure and Lustre Series

**Premium Finish:** Wonderkote and Eartscapes Series

**Professional Finish:** Pro Kote and Renewal Series

**Builder's Legacy Finishes:** Master Kote, Velvet Armor, and Premium Smooth Hi-Build.

## **APPLICATION**

Apply by airless spray for best results. May be applied by brush or roller; however, all properties related to hide and appearance may be affected. Surfaces should be dry prior to paint application. All products are formulated ready for application. If needed, thin sparingly and do not exceed 2oz per gallon. Clean all applicators with water immediately after use.

## **EQUIPMENT REQUIREMENTS**

**Airless:** Minimum .70 GPM, 2800 PSI, .019-.023" Tip

**HVLP:** Not Recommended

**Roller:** ¼"-½" nap synthetic shed-resistant

**Brush:** 100% Nylon or Synthetic Blend