



BUILDER'S LEGACY

PREMIUM SMOOTH HI-BUILD

352

ADVANTAGE SERIES
INTERIOR
FLAT FINISH
352
PREMIUM SMOOTH HI-BUILD

PREMIUM SMOOTH HI-BUILD is our finest primer/finish designed to set the standard for finishing new construction drywall. This high-building finish can produce the equivalent of 2 coats of paint in a single pass allowing contractors to prime, seal, and finish in the same day. By combining smooth application with seamless touch-up, this product is ideal for new construction and remodeling projects with tight timelines. The durable, stain-resistant finish allows for easy ongoing maintenance for owners and property managers.

PREMIUM SMOOTH HI-BUILD is designed for production and long-term durability. LEED v4 compliance, exceptional film build and excellent touch-up make this product ideal for high-end residential, multi-unit, mixed-use, and commercial projects. Can be applied to drywall, plaster, and masonry surfaces.

COMPLIANCE & CERTIFICATION

Gloss Level	1
VOC Content	< 5 g/L < 0.042 lb./Gal

RECOMMENDED USAGE

- For Interior Use on New Drywall
- Efficient Spray Application
- Use in High-End Residential, Multi-Unit, Mixed-Use, and Commercial Construction

PERFORMANCE & FEATURES

- Exceptional Film Build
- Excellent Durability
- Seamless Touch-up
- Maintenance Friendly Finish
- Single Product System
- Can Help Meet LEED v4 Credits

BENEFITS

High-Building Primer/Finish: Self-sealing properties and high-build, single coat coverage minimize surface imperfections which means fewer repairs and less time spent on the job site.

LASTING PERFORMANCE: Exceptionally tough finish has the durability of higher-sheen products with the aesthetic advantages of a flat finish. Great stain release, burnish resistance, and scrubbability provides livable finish for years to come.

VERSATILE APPLICATION: Easy application allows for this product to be sprayed on large jobs, rolled on small jobs, and quickly touched up for easy ongoing property maintenance. Low odor waterborne finish minimizes impact when painting in occupied spaces.

PRODUCT SPECIFICATIONS

Vehicle Type: Ethylene-Vinyl Acetate

Color Tinting: Pro White. May be tinted, up to 2 oz. per gallon, with low/zero VOC colorants.

Gloss: Flat. 1-4 units @ 60°

Solid Content: Weight: 59% ± 2
Volume: 40% ± 2

Drying Time: (75° F. & 50% R.H.)

To touch: 1 Hour

To recoat: Overnight

Extended drying time may be expected when conditions such as high humidity, high dew point, low temperature, etc. are present. Allow product to dry thoroughly before top coating

Theoretical Coverage:

Apply at 160 sq. ft./gal. to achieve
10.0 mils Wet Film Thickness
4.0 mils Dry Film Thickness

When calculating working coverage, allow for application losses, texture and porosity of surface, application technique, etc.

PRECAUTIONS/LIMITATIONS

- Please refer to Safety Data Sheets.
- Do not apply to "hot" plaster.
- Apply only if surface and paint temperatures are above 50° F and will remain so for 48 hours. Dew point must not be within 5° of the temperature until film is dry.



BUILDER'S LEGACY

PREMIUM SMOOTH HI-BUILD

352

ADVANTAGE SERIES
INTERIOR
FLAT FINISH
352
PREMIUM SMOOTH HI-BUILD

SURFACE PREPARATION

Surfaces must be dry, clean and free of dust, dirt, grease, oil or any other contaminants that may prevent proper adhesion. All loose paint must be removed and glossy surfaces dulled by sanding. Plaster surfaces must be well cured, and porous masonry surfaces should be filled with block filler. Tape joints and nailheads on drywall should be sanded and dusted clean before finishing. Mud on joints and nailheads must be thoroughly cured before finishing to help avoid photographing. Galvanized surfaces shall have all oils removed prior to application of coating.

Warning! If you scrape, sand or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage, especially in children. Pregnant women should also avoid exposure. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the national lead information hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

HALLMAN LINDSAY PRIMING RECOMMENDATIONS

Drywall: Self-prime and finish (two coats required).

Plaster/Masonry: GRIPCRETE Masonry/Plaster Primer, 166. Wood: Enamel Undercoat, 231.

Galvanized Surfaces: METALGUARD DTM Acrylic Primer/Finish, 338.

Steel Surfaces: METALGUARD Rust Inhibitive Primer, 330.

Block: GRIPCRETE Block Filler, 184 or Masonry Surfacer, 179.

APPLICATION

Apply by airless spray and back roll with a ½ to 1 inch nap roller for best results. May be applied by brush or roller; however, all properties related to hide and appearance may be affected. Surfaces should be dry prior to paint application. All products are formulated ready for application. If needed, thin sparingly and do not exceed 2oz per gallon. Clean all applicators with water immediately after use.

EQUIPMENT REQUIREMENTS

Airless: Minimum 1.20 GPM, 3000 PSI, .023-.027" Tip

HVLP: 3-4 stage turbine, 6-8 PSI, .051 to .070 projector set

Roller: ½"-1" nap synthetic cover

Brush: 100% Nylon or Synthetic Blend