



BUILDER'S LEGACY

PRO DRYWALL PRIMER

368

PERFORMANCE SERIES
INTERIOR
PRIME COAT
368
PRO DRYWALL PRIMER

PRO DRYWALL PRIMER is a specialized first coat product designed for preparing uncoated drywall for texturing. Formulated to create uniform porosity between joint compound and face paper, they produce an even base promoting a better texture uniformity. These primers are built for professional application to help reduce joint banding and photographing.

PRO DRYWALL PRIMER is a production grade primer designed to help produce a uniform surface on commercial and residential drywall. The off-white formulation improves wet and dry hide, while the contrast allows applicators to easily spot check texture consistency. Formulated specifically for priming under texture, it is not intended for use under wall coverings.

COMPLIANCE & CERTIFICATION

Gloss Level	1
VOC Content	< 5 g/L < 0.042 lb./Gal

RECOMMENDED USAGE

- For Interior New Drywall
- Ideal for Priming Prior to Texture and/or Under Flat or Lo-Sheen Finishes.
- Use in Residential and Commercial New Construction

PERFORMANCE & FEATURES

- Improved Texture Application
- Consistent Textured Finish
- Ideal for Flat Finishes
- Can Help Meet LEED v4 Credits

BENEFITS

Improved Consistency: Formulated to seal drywall prior to texturing. The stock off-white color allows for easier spot-checking of texture consistency during application.

Acceptable Finish Coats: Designed specifically for application under texture products, it provides a good seal for flat finishes only.

Environmentally Responsible Product: This zero-VOC finish meets the performance needs of contractors, specifiers, and general contractors looking to meet the strictest air quality standards.

PRODUCT SPECIFICATIONS

Vehicle Type: Ethylene-Vinyl Acetate

Color Tinting: Off White

Gloss: Flat

1-2 units @ 60°

Solid Content: Weight: 59% ± 2

Volume: 38% ± 2

Drying Time: (75° F. & 50% R.H.)

To touch: 1 Hour

To recoat: 2 Hours

Extended drying time may be expected when conditions such as high humidity, high dew point, low temperature, etc. are present. Allow product to dry thoroughly before top coating

Theoretical Coverage:

Apply at 200 sq. ft./gal. to achieve

6.0 mils Wet Film Thickness

2.3 mils Dry Film Thickness

When calculating working coverage, allow for application losses, texture and porosity of surface, application technique, etc.

PRECAUTIONS/LIMITATIONS

- Please refer to Safety Data Sheets.
- Apply only if air, surface and material temperatures remain 50° F or above during application and drying.



BUILDER'S LEGACY

PRO DRYWALL PRIMER

368

PERFORMANCE SERIES
INTERIOR
PRIME COAT
367-3
PRO DRYWALL PRIMER

SURFACE PREPARATION

Surfaces must be dry, clean and free of dust, dirt, grease, oil, chalk, efflorescence or any other contaminants that may prevent proper adhesion. Tape joints and nailheads should be sanded and dusted clean before finishing. Mud on joints and nailheads must be thoroughly cured before finishing to help avoid photographing.

Warning! If you scrape, sand or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage, especially in children. Pregnant women should also avoid exposure. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the national lead information hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

HALLMAN LINDSAY FINISHING RECOMMENDATIONS

Professional Finish: Pro Kote and Renewal Series

Builder's Legacy Finishes: Master Kote, Velvet Armor, and Premium Smooth Hi-Build.

APPLICATION

Mix thoroughly before use. Apply by brush, roller, or airless spray or conventional spray. Flow and leveling is best achieved by applying a full, uniform coating and working to a wet edge using overlapping strokes. Do not brush or roll excessively. Surfaces should be dry prior to paint application. Reducing material for spray application should not exceed 10%. All products are formulated ready for application. If needed, thin sparingly and do not exceed 2oz per gallon. Clean all applicators with water immediately after use.

EQUIPMENT REQUIREMENTS

Airless: Minimum .70 GPM, 3000 PSI, .019-.023" Tip

HVLP: Twin-stage turbine, 5-8 PSI, .051 to .070 projector set

Roller: ½" - 1" nap synthetic cover

Brush: 100% Nylon or Synthetic Blend