



PROFESSIONAL

**INTERIOR**

**SEALZ-IT**  
ALKYD STAIN BLOCKING PRIMER



**GREAT PAINT GREAT PEOPLE**



hallmanlindsay.com



# SEALZ-IT

SEALZ-IT is a fast-drying alkyd primer/sealer formulated to prime and seal a variety of new and previously coated surfaces. Quick-dry solvents allow for finishing in as little as an hour for faster job completions. Alkyd resin system creates a strong seal to block out water stains, nicotine stains, tannins when spot priming exterior wood, and much more. Formulated to be a quick-fix solution to stains and priming needs, it is not intended to replace the benefits of premium and specialty primers.

Apply SEALZ-IT to lock-in stains and odors on a variety of new and previously painted surfaces: wood, plaster, drywall, hardboard, masonry, water-damaged walls, ceilings, trim, and other porous surfaces. May be used to prime surfaces prior to receiving vinyl wall coverings.

## FEATURES

- Quick Dry Solvent
- Stain Blocking Primer
- Easy Sanding
- Improved Coverage

## BENEFITS

### Quick Dry Alkyd

Solvent base allows for excellent blocking of stains including water damage, crayon, marker, and many others.

### Easy Sand Formula

The easy sand feature makes it great for use on painted trim, molding, and cabinets.

### High Hiding

The higher solids formulation provides great wet and dry hide giving a superb walk away appearance.



BLOCKS MARKERS & CRAYONS



EXCELLENT STAIN BLOCKING



GREAT FOR WATER STAINS

## TECHNICAL INFORMATION

### APPLICATION INFORMATION

Drying Time at 77° F 50% R.H:

To Touch: 30 minutes\*

Recoat: 1 hour\*

\* Cooler temperatures and higher relative humidity will extend dry times

Recommended Spreading Rate:

400 sq. ft./gal to achieve  
4.0 mils WFT; 1.7 mils DFT

Solids Content:

Volume: 42% ± 2 Weight: 63% ± 2

### BASES: WHITE - 525 SERIES

### EQUIPMENT RECOMMENDATIONS

Roller: ½" – ¾" nap shed-resistant cover or lambswool cover

Brush: Natural china bristle or synthetic blend

Airless: Minimum 1/2 GPM with .015-.17" tip @ 2500-2700 PSI

HVLP: Twin-stage turbine, 5 – 8 PSI, .051 to .070 projector set

### SAFETY AND COMPLIANCE

VOC (EPA Method 24):

Under 450 g/L 3.75 lb./Gal

### FINISHING RECOMMENDATIONS

Interior Finishes: Compatible with all Hallman Lindsay interior finishes.

Exterior Finishes: Compatible with all Hallman Lindsay exterior finishes.

